

6

5

4

3

2



1

REVISION


ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	B1	UPDATED PER ECO-14033	12/4/2024	HBAKKE	REVANGELIS



"P1"
USB 3.2 TYPE A PLUG



"P2"
USB 3.2 MICRO-B 90° PLUG



USB 3.0 HIGH FLEX CABLE
JACKET: PVC, BLACK
NOM DIA.: .217" [5.5]

PART NUMBER	LENGTH METERS [FT]
AOC-U30AMIM-C1R-005	05 [16.4]
AOC-U30AMIM-C1R-008	08 [26.3]
AOC-U30AMIM-C1R-010	10 [32.8]
AOC-U30AMIM-C1R-015	15 [49.2]
AOC-U30AMIM-C1R-020	20 [65.6]
AOC-U30AMIM-C1R-030	30 [98.4]

NOTES:

- CABLE TYPE-U DRAG CHAIN TESTING:
5 MILLION CYCLES MIN.(75mm BEND RADIUS)
- CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:
X = ±.2 [5] | FRACTIONS ± 1/32
.XX = ±.02 [0.5] | ANGLES ± 1°
.XXX = ±.005 [0.13]

CABLE LENGTH TOLERANCES:
≤12 [305] = +1 [25] / -0
>12 [305] ≤ 60 [1524] = +2 [51] / -0
>60 [1524] ≤ 120 [3048] = +4 [102] / -0
>120 [3048] ≤ 300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY
AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES
MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

L-com
an INFINIT@ brand

Website: www.L-com.com
Phone: 1.800.341.5266 | 1.978.682.6936



INTERPRET ALL DIMENSIONS AND
TOLERANCES PER ASME Y14.5

SCALE NONE | SHEET 1 OF 1

DESCRIPTION

USB 3.2 GEN 1 ACTIVE OPTICAL CABLE, A MALE TO MICRO-B
MALE DRAG CHAIN JACKET W/ SCREW, RIGHT ANGLE, 5Gps

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	VTHANGARAJ	AOC-U30AMIM-C1R	B1

6

5

4

3

2

1