


LENGTH CODE CHART		
CABLE# & LENGTH	LENGTH SYMBOL	EXAMPLES OF PART# USED
CA-RTPRTJAXXX	WHERE XXX = LENGTH IN FEET	CA-RTPRTJA010 (10 FEET)
CA-RTPRTJANXX	WHERE NXX = LENGTH IN INCHES	CA-RTPRTJAN16 (16 INCHES)
CA-RTPRTJAMXX	WHERE MXX = LENGTH IN METERS	CA-RTPRTJAM07 (7 METERS)
CA-RTPRTJAXMX	WHERE XMX = LENGTH IN DECIMEL METERS	CA-RTPRTJA3M5 (3.5 METERS)

- NOTES:
1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY
 2. CABLE ASSEMBLY SHALL RECIEVE INSERTION LOSS TEST#TP-0027
 3. CABLE ASSEMBLY SHALL WITHSTAND PULL TEST OF 40lbs WITHOUT ANY SEPERATION OR ELECTRICAL FAILURE
 4. CABLE SHALL BE RoHS COMPLIANT
 5. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031
 6. CENTER PIN OF CONNECTORS TO BE SOLDERED OR CRIMPED ONTO CABLE INNER CONDUCTOR

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES

OVERALL CABLE LENGTH TOLERANCE

≤12 [305] = +1 [25]/-0
 >12 [305] ≤ 60 [1524] = +2 [51] /-0
 >60 [1524] ≤120 [3048]=+4/-0
 >120 [3048] |U+2264300 [7620] =+6/-0
 >300 [76290]=+5%/-0

C	HL_4177	08/11/09	Changed Length Reference Points To Outside Ends of Connectors
B	HL-ECN-0037	05/11/09	Change Tol. for Heatshrink from ±.06" & ±.15mm
REV	ECN No.	DATE	DESCRIPTION
			

SIZE		TITLE:			
A		FABRICATION: CA-195R SERIES RP-TNC PLUG TO RP-TNC JACK ASSEMBLY with HEATSHRINK			
		DRAWN BY	B.Puchaski	08/11/09	DRAWING No.
ORIGINATOR		B.Puchaski	08/19/08	F973	C
APPROVAL		M. Audus	08/11/09	PART No.	CA-RTPRTJA ^{VAR.}
SCALE 1:1	SHEET 1/1	MATERIAL	Noted	FILE No.	F973-01

Website: www.L-com.com
 Tel: 1-800-343-1455
 Copyright © 2009 L-com, Inc.
 All rights reserved.