



LENGTH CODE CHART		
CABLE# & LENGTH	LENGTH SYMBOL	EXAMPLES OF PART# USED
CA4NMRTFXXX	WHERE XXX = LENGTH IN FEET	CA4NMRTF(10 FEET)
CA4NMRTFNXX	WHERE NXX = LENGTH IN INCHES	CA4NMRTFN16 (16 INCHES)
CA4NMRTFMXX	WHERE MXX = LENGTH IN METERS	CA4NMRTFM07 (7 METERS)
CA4NMRTFXMX	WHERE XMX = LENGTH IN DECIMEL METERS	CA4NMRTF3M5 (3.5 METERS)

**NOTES:**

1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY
2. CABLE ASSEMBLY SHALL RECIEVE INSERTION LOSS TEST#TP-00079
3. CABLE ASSEMBLY SHALL WITHSTAND PULL TEST OF 40lbs WITHOUT ANY SEPERATION OR ELECTRICAL FAILURE
4. CABLE SHALL BE RoHS COMPLIANT
5. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031
6. CENTER PIN OF CONNECTORS TO BE SOLDERED OR CRIMPED ONTO CABLE INNER CONDUCTOR

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES  <u>OVERALL CABLE LENGTH TOLERANCE</u>  $\leq 12$ [305] = +1 [25]/-0 $>12$ [305] $\leq 60$ [1524] = +2 [51]/-0 $>60$ [1524] $\leq 120$ [3048] = +4/-0 $>120$ [3048] [U+2264300 [7620] = +6/-0 $>300$ [76290] = +5%/-0				A	TITLE: FABRICATION: CA-400 SERIES N-MALE TO RP-TNC PLUG ASSEMBLY with HEATSHRINK				
	D	4432	12/09/09						Changed Note#2 TP-00027 to TP-00079
	C	HL_4177	08/11/09		Changed Length Reference Points To Outside Ends of Connectors				
	B	HL-ECN-0037	05/11/09		Change Tol. for Heatshrink from ±.06" & ±.15mm				
	REV	ECN No.	DATE	DESCRIPTION	DRAWN BY	B.Puchaski	12/09/09	DRAWING No.	REV
					ORIGINATOR	B.Puchaski	11/19/08	F993	D
Website: www.L-com.com Tel: 1-800-343-1455 Copyright © 2009 L-com, Inc. All rights reserved.					APPROVAL	M. Audus	08/11/09	PART No. CA4NMRTF	VAR-
					SCALE 1:1	SHEET 1/1	MATERIAL Noted	FILE No. F993-01	