




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
-	APPROVED FOR PRODUCTION BY ZIG WORONKO	10/13/99	BJD
A	REDRAWN FROM MAC 98-083102, AND NEW FORMAT	8/6/09	D.FRISIELLO



NOTES:

1. THIS GENDER CHANGER HAS TWO MALE 50-CONTACT MICRO-RIBBON CONNECTORS THAT ARE WIRED STRAIGHT THROUGH, PIN TO LIKE-NUMBERED PIN.
2. THE STEEL HOUSING PROVIDES COMPLETE 360° SHIELDING.
3. INSULATOR MATERIAL IS GLASS-FILLED PBT.
4. CONNECTOR CONTACTS ARE GOLD PLATED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] DIMENSIONAL TOLERANCES: .X = ±.1 .XX = ±.03 .XXX = ±.005 ANGULAR TOLERANCES: ALL = ± 1° PROJECTION	APPROVALS D.FRISIELLO	DATE 8/6/09		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	CHECKED BY M.MARTINEZ	8/6/09		CATEGORY DATA	
	APPROVED BY S.SMITH	8/6/09	PRODUCT DESCRIPTION 50 POSITION M MICRORIBBON SOCKET SAVER		
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321	DWG. NO. DGC50M
SCALE: NONE		CAD FILE: DGC50M.SLDDRW			SHEET 1 OF 1

