


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	05/26/2022	DGUTTADAURO



NOTE

- VOLTAGE RATING:40VAC; CURRENT RATING: 0.5A
OPERATING TEMPERATURE RANGE: -20°C ~+70°C
- ALL CONNECTORS HAVE NICKEL PLATED SHELLS AND GOLD FLASH PLATED CONTACTS.
- ALL DIMENSIONS ARE FOR REFERENCE ONLY.
- ADAPTOR SHALL BE 1080P@60Hz FUNCTIONAL TESTED PRIOR TO SHIPPING.
- ADAPTOR SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] FRACTIONS ± 1/32 .XX = ± .02 [.5] ANGLES ± 1° .XXX = ± .005 [.13]	APPROVALS	DATE	 50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936
	DRAWN BY BZHANG	05/24/2022	
CHECKED BY KGU	05/24/2022	PRODUCT DESCRIPTION DP M TO DVI-IDL F ADAPTER	
APPROVED BY DGUTTADAURO	05/24/2022		SIZE A CAGE CODE 43321 DWG. NO. DPDVIAD REV. A
THIRD-ANGLE PROJECTION	COLOR VARIATIONS MAY OCCUR	SCALE: NONE	CAD FILE: DPDVIAD.SLDDRW