


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	10/24/11	D.GRIFFIN



3 EQ. SP. @ 1.00 = 3.00  
TOLERANCE NON-CUMULATIVE

2X, PANEL FASTENER

DETAIL A

**RoHS Compliant** ✓

NOTES:

1. PANEL MATERIAL: .06 THK COLD ROLLED STEEL.  
PANEL FASTENER: THERMOPLASTIC.
2. FINISH: BLACK POWDER COAT.
3. RECOMMENDED MOUNTING HOLE FOR MATING FASTENER,  $\phi .252 +.002/.000$
4. COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D.FRISIELLO	10/21/11		
ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 .XX = ± .02 .XXX = ± .005	CHECKED BY M.SEDLESKI	10/21/11	CATEGORY FIBER OPTIC SUB PANELS	
	APPROVED BY M.MARTINEZ	10/21/11	PRODUCT DESCRIPTION FSP SUBPNL, KEYSTONE OPENINGS	
PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	COLOR VARIATIONS MAY OCCUR	SIZE <b>A</b>	FSCM NO. <b>43321</b>
			DWG. NO. FSP-KYSTN-BNK	REV. <b>A</b>
			SCALE: NONE	CAD FILE: FSP-KYSTN-BNK.SLDDRW
				SHEET 1 OF 1