	8	7		6	1	5	*	4		3		2		1	_
	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE							ZONE	REV	DESCRIPTION	REVISION	DATE	CHANGED BY	APPROVED	-
	WITHOUT THE WRITTEN PERM	ISSION OF L-COM, INC. IS PROF	HIBITED.					ZONL	A	NITIAL RELEASE		06/28/2024	SLI	WLI	1
D					-■		1.18 [30]								D
	_	75		.57 [14.5]											
С			/	[14.0] ¥				H		Ŕ	BNC PL	UG			С

# NOTES:

В

А

# MATERIALS:

SHELL: BRASS CONTACTS: BRASS INSULATOR: PTFE

#### FINISH:

SHELL: NICKEL CONTACT: GOLD

ELECTRICAL: CHARACTERISTIC IMPEDANCE: 75 OHM

APPLICATION NOTES: RESISTOR; 1/2 WATT METAL FILM TYPE

### PACKAGING:

8

TERMINATOR SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

### **REGULATORY COMPLIANCE:**

EU ROHS DIRECTIVE (MOST RECENT RELEASED VERSION)

7

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]	APPROVALS	DATE						h Street, West Mill, Andover, MA 01845 USA		
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0	DRAWN BY SLI	06/28/2024	Phone: 1.800.341.3 1.978.682.6					0.341.5266 8.682.6936		
>12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0	CHECKED BY WLI	06/28/2024								A
>120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0	APPROVED BY WLI	06/28/2024								
ALL OTHER DIMENSIONAL TOLERANCES:   .X = ± .2 [5] FRACTIONS   .XX = ± .02 [.5] ± 1/32   .XXX = ± .005 [.13] ANGLES ± 1°	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION 75 OHM BNC MALE TERMINATOR							
THIRD-ANGLE PROJECTION	COLOR VARIATIONS		SIZE	CAGE	CODE	ITEM NO.			REV.	
	MAY OC		Α	433	321		LCC40500	03	A	
	REF		SCALE:	SCALE: NONE CAD FILE: LC		ILE: LCC40500	E: LCC405003.SLDDRW		1 OF 1	
4	3				2			1		

В

T-Rev.D1

6

5