

TNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable



EZ-240-TM-X-LC



Times Microwave Systems Connector Specification

Configuration

- TNC Male Connector
- 50 Ohms
- Straight Body Geometry
- LMR-240, LMR-240-DB, LMR-240-FR, 240-Series Interface Type
- Crimp/Non-Solder Contact Attachment

Features

- Designed to industry standard interface dimensions
- Quality body materials and plating
- Crimp/Non-Solder Contact attachment
- Operates to 6 GHz

Applications

- RF Boxes and components
- RF Test systems
- General Purpose RF Interconnect
- Laboratory applications

Description

L-com's TNC Male connector for LMR-240, LMR-240-DB, LMR-240-FR and 240-Series coax uses a Crimp/Non-Solder Contact attachment method. This TNC connector is one of the many RF coaxial connectors in L-com's product line up and like all our products, they will ship the same day. Our TNC Male connector operates up to a maximum frequency of 6 GHz.

The specifications and a basic dimensional drawing for EZ-240-TM-X-LC Male TNC connector can be found in this datasheet PDF. L-com's portfolio of RF and microwave connectors allows users to choose from a large number of options when building assemblies to fit their RF interconnect needs. RF cables can be created to fulfill many interconnect applications ranging from In the Box hookup, test equipment connectivity or as part of a system installation. In addition to an offering of RF connectors and coaxial cable L-com offers both standard and custom cable assemblies to fit a customer's specific needs.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|--------------------------------------|---------|---------|---------|-------|
| Frequency Range | DC | | 6 | GHz |
| VSWR | | | 1.25:1 | |
| Operating Voltage (AC) | | | 500 | Vrms |
| Dielectric Withstanding Voltage (AC) | | | 750 | Vrms |

Mechanical Specifications

Size

| | | |
|------------|---------|-----------|
| Length | 1.31in | [33.27mm] |
| Width/Dia. | 0.594in | [15.09mm] |
| Weight | 0.05lbs | [22.68g] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[TNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable EZ-240-TM-X-LC](#)

TNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable



EZ-240-TM-X-LC



| | | |
|---------------|-----------|----------|
| Mating Cycles | 500Cycles | |
| Mating Torque | 20in-lbs | [2.26Nm] |

Material Specifications

| Description | Material | Plating |
|--------------|-----------------|------------------------------|
| Contact | Phosphor Bronze | Gold 50μ in. minimum |
| Insulation | Teflon | |
| Body | Brass | Tri-Metal 80μ in. minimum |
| Coupling Nut | Brass | Tri-Metal 80μ in. minimum |

Environmental Specifications

| | |
|--------------------|-----------------|
| Temperature | |
| Operating Range | -55°C to +155°C |

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data


TNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable EZ-240-TM-X-LC

URL: <https://www.l-com.com/tnc-male-connector-crimp-non-solder-contact-attachment-lmr-240-lmr-240-db-lmr-240-fr-240-series-cable-ez-240-tm-x-lc-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

TNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable

L-com CAD Drawing



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:
 .X ± .2 [5.08] FRACTIONS ± .132
 .XX ± .02 [.51] ANGLES ± 1°
 .XXX ± .005 [.13]

CABLE LENGTH (L) TOLERANCES:
 L ≤ 12 [305] = +.1 [25] / -0
 12 [305] < L ≤ 60 [1524] = +.2 [51] / -0
 60 [1524] < L ≤ 120 [3048] = +.4 [102] / -0
 120 [3048] < L ≤ 300 [7620] = +.6 [152] / -0
 300 [7620] < L = +.6% L / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

THIRD-ANGLE PROJECTION

L-com™
 an INFINITE brand
 50 High Street, West Mill, 3rd Floor, Suite #30
 North Andover, MA 01845, USA
 Phone: 1.800.341.5266 | 1.978.682.6936
 Fax: 1.978.689.9484
 Website: www.L-com.com
 E-mail: CustomerService@L-com.com

SCALE: N/A

SHEET 1 OF 1

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

PART NUMBER: EZ-240-TM-X-LC

DRAWN BY: BPUCHASKI

CAGE CODE: A 43321

REV: A