



## UC1284B

### USB to (IEEE 1284) Printer Port Converter

- Fully bidirectional ensuring compatibility with the latest printers
- Fully compliant with the USB 1.1 specification
- One C-36 parallel connector, one USB type A connector

#### Features

- Full bidirectional to ensure compatibility with today's latest printers
- Non-powered
- 1 USB Type A connector for standard USB cable connection
- 1 C-36 parallel connector
- Fully compliant with USB Spec. Ver. 1.1
- Supports standard PC parallel port register based operation
- Supports multiple printers with multiple parallel adapters
- Max. Throughput: 1.2 Mbits/Sec (ECP Mode)

#### Specifications

Function		Specification
Connectors	Input	USB Type A Plug
	Output	Centronics 36 pin Male
Cable Length		180 cm (6')
Power Mode		Bus Powered (via the Cable)
Housing		Plastic
Weight		110g
Dimension (L x W x H)		63 x 46 x 17mm
Operating Temperature		5-40°C
Storage Temperature		-20-60°C
Humidity		0~80% RH, Non-condensing

ATEN.com is published by ATEN International Co. Ltd., Taiwan. All rights reserved.

The specifications and pictures are subject to change without notice.  
All trademarks and logos are the properties of their respective holders.

Distributed by:

 **L-com** Global  
Connectivity

50 High St., West Mill, Suite #30  
North Andover, MA 01845  
www.L-com.com  
E-mail: sales@L-com.com  
Fax: 978-689-9484  
Toll Free: 800-343-1455